

30Z200

Radial Leaded PTC Resettable Fuse

Summary

- RoHS Compliant (Lead Free) Product

- Applications: Wide variety of electronic equipment
- Product Features: Low hold current, Solid state, Radial leaded product ideal for up to 30V
- Operation Current: 2.0A
- Maximum Voltage: 30V
- Temperature Range : -40°C to 85°C

Electrical characteristics (23°C)

Part Number	Hold Current	Trip Current	Max.Time to Trip	Maximum Current	Rated Voltage	Typical Power	Resistance Tolerance	
							RMIN	RMAX
	IH, A	IT, A	at 5xIH	IMAX, A	VMAX, Vdc	Pd, W	ohms	ohms
30Z200	2.0	4.0	10.5	40	30	1.0	0.02	0.045

IH - Hold current-maximum current at which the device will not trip at 23 °C still air.

IT - Trip current-minimum current at which the device will always trip at 23°C still air.

VMAX - Maximum voltage device can withstand without damage at its rated current.

IMAX - Maximum fault current device can withstand without damage at rated voltage (VMAX).

Pd - Typical power dissipated from device when in tripped state in 23°C still air environment.

RMIN - Minimum device resistance at 23°C.

RIMAX - Maximum device resistance at 23 °C, 1 hour after tripping .


Physical specifications:

Lead material: Tin plated copper, 24 AWG.

Soldering characteristics: MIL-STD-202, Method 208E.


Insulating coating: Flame retardant epoxy, meets UL -94V-0 requirement.

Production Dimensions (millimetre)



Part Number	A	B	C	D	E	Lead
	Maximum	Maximum	Typical	Minimum	Maximum	Φ
30Z200	10.2	15.7	3.0	7.6	5.1	0.6

Thermal Derating Curve



Typical Time-To-Trip at 23°C

